

PRIMO[®] EL PLUS Premium Seat with Active Weight Adjustment



PRIMO[®] EL PLUS Technical data

Premium seat

The low-frequency suspension with travel of 110 mm in the Primo EL Plus delivers outstanding comfort despite the seat's low height. Its premium package of comfort-enhancing features includes passive seat climatization and active pneumatic weight adjustment, which is very advantageous with frequently changing drivers. The seat automatically sets itself to the operator's weight to maximize vibration attenuation. Integrated heating and a mechanical lumbar support are included as standard features. The seat meets the latest safety requirements and is equipped with a seat and belt contact switch as well as a duosensitive ELR-belt system with orange belt straps as standard.



Mechanical mbar support

Passive

climate system

T۲ Electronic weight adjustment

PRIMO® EL PLUS

Fea	tures	PRIMO [®] EL PLUS
	ARTICLE NO.	
	Fabric, compressor 12V	1492114
_	STANDARD FEATURES	
_	Shock absorber, nonadjustable	•
_	Pneumatic suspension with 12 V compressor	•
_	Low-frequency suspension	•
	Suspension stroke, 70 mm	•
	Weight adjustment, electronic, 45–170 kg	•
	Height adjustment, 40 mm	•
	Climate system, passive	•
1	Fore/aft adjustment, 210 mm	•
2	Lumbar support, mechanical	•
3	Adjustable backrest angle	•

Measurements (installation dimensions)

4 ELR-belt system, duosensitive, orange belt Belt buckle with contact switch Seat cushion width 520 mm 5 Seat heating Combined seat cushion depth-angle adjustment 6 Operator presence switch (OPS) • **OPTIONAL FEATURES** 7 Document box 0 8 Armrests, adjustable angle, 60 mm x 320 mm 0 Fore/aft isolator * 0 9 Backrest extension, integrated 0

* Fore/aft isolator not for earth-moving machinery

 STANDARD FEATURES **OPTIONAL FEATURES**

611 mm 665 mm Fore/aft adjustment 120 90 32 Suspension stroke 653 mm 270 mm 35 😪 GRAMMER 212 mm 224 mm 328 mm 23 All dimensions in mm. 520 mm 280 mm

Subject to technical changes.