

PRIMO[®] M Standard Seat with Mechanical Suspension



PRIMO[®] M Technical data

Standard seat

This seat's mechanical suspension with reduced suspension travel of 60 mm effectively buffers vibrations in even the smallest cabs. The upper seat section is designed to deliver comfort from the word go. The focus is on the most important adjustments, including a mechanical lumbar support and mechanical weight setting feature.





Features PRIMO[®] M ARTICLE NO. Fabric 1293486 Imitation leather 1091028 **STANDARD FEATURES** Shock absorber, nonadjustable • Suspension, mechanical Suspension stroke , 60 mm 1 Weight adjustment, manual, 45-170 kg • 2 Fore/aft adjustment, 210 mm • 3 Lumbar support, mechanical • 4 Adjustable backrest angle •

	PRIMO [®] M
Seat cushion width	470 mm
OPTIONAL FEATURES	
Document box	0
Armrests, adjustable angle,	
60 mm x 320 mm	0
Fore/aft isolator*	0
Backrest extension, integrated	0
ELR-belt system, duosensitive	0
Seat heating	0
Operator presence switch (OPS)	0
	OPTIONAL FEATURES Document box Armrests, adjustable angle, 60 mm x 320 mm Fore/aft isolator* Backrest extension, integrated ELR-belt system, duosensitive Seat heating

OPTIONAL FEATURES

* Fore/aft isolator not for earth-moving machinery

• STANDARD FEATURES

Measurements (installation dimensions)

599 mm 608 mm 470 mm 584 mm Fore/aft adjustment 120 90 ORAMMER 315 mm 608 mm 8 8 mm 213 4 801 164 mm 284 mm 328 mm 249 mm All dimensions in mm. 470 mm Subject to technical changes. 54 83